

## **RCR12 Series**

48", 60", 72": 20-50 HP RCR1248, RCR1260, RCR1272 Cat. 1

Working Width (cm) 48" (122), 60" (152), 72" (183)

Overall Width 53". 64". 76" Overall Length 89", 103", 114"

Weight - Ib (kg) 400 (181), 478 (217), 564 (256)

Cutting Height 1-1/4" - 10" Cutting Capacity 1" Diameter Deck Thickness 12 Gauge Deck Height 7-1/4"

Safety Guards Front and Rear Rubber Guards

Skids 1/4" x 2" Weld on

Blades 1/2" x 3" Heat Treated Alloy Steel

Free Swinging Blades

Blade Tip Speed 13,256 fpm, 16,536 fpm, 15,033 fpm

Dishpan Round 10 Ga. x 24" Diameter,

Dish Shaped

Gearbox 540 RPM

PTO Driven Gearbox Cast Iron Housing

Driveline ASAE Cat. 3

Standard - 1/2" **Shear Bolt Protection** Optional - Bolt 2 Plate

Slip Clutch

Tailwheel 15" Laminated Tire

w/Cast Iron Hub

\* See dealer for complete warranty information.

**Color Options:** 











- Floating 3-point permits deck to hug the terrain
- · Fully welded deck to side skirt
- · Dishpan with dual blades
- · 360 Degree swivelling tailwheel
- Optional bolt on skid shoes for 60" & 72"