



## RBT60 Series

Features	Benefits
<b>Warranty</b>	One year parts and labor. See warranty page for complete details.
<b>10 ft &amp; 12 ft (3.05m &amp; 3.66m) working widths</b>	Choice of two sizes to pick from. Both sizes handle large capacities.
<b>High hp range</b> <b>2-Wheel drive</b> <b>4-Wheel drive</b>	225 Hp (167.8 kW) with 10 ft (3.05m) blade & 175 hp (130.5 kW) with 12 ft (3.66m) blade 200 Hp (149.1 kW) with 10 ft (3.05m) blade & 160 hp (119.3 kW) with 12 ft (3.66m) blade
<b>Cat. II and Cat III 3-point hitch</b>	Can go from Cat. II to Cat. III 3-Point tractor. Enables a wider variety of tractors to be used.
<b>Quick hitch compatible</b>	Compatible with Land Pride QH20 Cat. II Quick hitch for easy attachment and removal. Increases productivity.
<b>Blade angles left and right up to 45 degrees hydraulically</b>	Allows the operator to set the blade at the angle of his choice to complete the job with satisfactory results.
<b>Blade offsets left and right up to 55" (1.40m) hydraulically</b>	Allows the operator to position the end of the moldboard beyond tractor tire and close to solid obstacles such as fences, buildings and abutments.
<b>Blade tilts up and down up to 15 degrees hydraulically</b>	Allows the operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches of various sizes.
<b>Mainframe is fully welded and reinforced</b>	Overall Mainframe strength is enhanced due to being fully welded.
<b>Heavy-duty pivot assembly with 4 1/2" (11.4cm) diameter solid steel moldboard kingpin</b>	1" (2.5cm) Plate steel turntable and 4 1/2" (11.4 cm) King pin for handling high torque in this area up to 225 hp (167.8 kW) 2-wheel or 200 hp (149.1 kW) 4-wheel drive tractors with 10 ft (3.05m) moldboard and 175 hp (130.5 kW) 2-wheel or 160 hp (119.3 kW) 4-wheel drive tractors with 12 ft (3.66m) moldboard.
<b>Formed 19" (48.3cm) high moldboard</b>	Can move a great deal of material in a short time.
<b>1/2" (13mm) Formed moldboard with 3/8" (10mm) formed channel reinforcement</b>	Makes it one of the strongest moldboards in its class for handling heavy loads.
<b>Retractable park stand</b>	Enables one person hook-up and keeps the mainframe off of the ground.
<b>Front pivot shaft has two grease points</b>	Helps front pivot shaft to move easily.
<b>Heavy-duty blade pivot assembly</b>	1" (2.5cm) Plate steel turntable and 4 1/2" (11.4cm) kingpin handle tremendous torque delivered by up to 225 hp (167.8 kW) tractors.
<b>Accessories</b>	
<b>Skid shoes</b>	Skid shoes protect moldboard from hitting low lying obstructions such as manhole covers.
<b>End plates</b>	End plates allow the blade to hold material in to drag from one spot to another.
<b>Dual gauge wheels</b>	Gauge wheels position the height of the blade to aid in grading.