

**RCD1884 Model**

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>5 Year gearbox warranty</b>	Shows our confidence in the gearbox integrity.
<b>Gearbox Seal Protection</b>	Gearbox bottom seal protection for longer bearing life.
<b>Cat. 3 main driveline with 2-plate slip-clutch</b>	2-Plate slip-clutch protect driveline and gearboxes. slip-clutch is more convenient than shear bolt for continual work.
<b>Shock absorbing flex-coupler between main and side gearboxes</b>	Protects intermediate drive shaft and side gearbox from hard objects in the blade path.
<b>10" Deck offset to the right</b>	Allows the operator to cut closer to bodies of water, drainage ditches, roadways and objects such as fence lines, guard rails, buildings, and trees.
<b>Lower clevis type 3-Point hitch</b>	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
<b>Smooth deck top</b>	Reduces accumulation of debris and is easier and faster to clean.
<b>Fully welded 10 gauge deck</b>	Fully welded deck adds additional strength to the deck. 10 Gauge decks can withstand more abuse than decks with lighter gauge.
<b>Box tubing deck supports</b>	Makes for a stronger rigid deck.
<b>Round back design</b>	Helps discharge grass better than enclosed or partially enclosed cutters.
<b>11 5/8" Deck Height</b>	Allows cutter to handle heavy cutting conditions.
<b>1 1/2" to 12" Cutting height</b>	Provides for a wide range of cutting conditions.
<b>Skid shoes</b>	Provides sidewall reinforcement and protection to bottom of sidewall.
<b>1/2" x 4" Heat-treated free swinging blades</b>	Free swinging protects from obstructions. Heat-treated offers longer life.
<b>1/2" x 4" Blade bar</b>	Heavy-duty blade bar adds support to stump jumper and gearbox output shaft.
<b>Splined blade bar hub</b>	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
<b>Stump jumper</b>	Standard round stump jumper slides over stumps, rocks, and debris.
<b>Front and rear guarding</b>	Protect against flying debris. Optional front rubber or single chain guarding. Standard rear metal band or optional rear extended metal guarding.
<b>Optional 15" Laminated tailwheel 4" x 16' Molded rubber</b>	Laminated material is long lasting in rough conditions and can't go flat. Can't go flat.